# **MAGNUM**6000 lb.

With Strap Bearings

### **Boat House**

## INSTALLATION INSTRUCTIONS


Boat Lifts Unlimited Odenton, Maryland 410-674-3100


### **Prior to installation:**

- a). To insure that the liftwill operate properly, Adequate electricity should be available. Electricity will also be needed to install the lift.
- b).If available ceiling joist are to be used, insure that they are not cracked or show any signs of decay.
- C). We recommend that he ceiling joist be doubled up 2 x 10 timbers.
- d). Obtain any required local permits.


DO NOT USE ANY POWER TOOL WHILE STANDING IN THE WATER. IF ELECTRICITY MUST BE USED NEAR THE WATER, INSURE THAT THE CIRCUIT IS PROTECTED BY A GROUNG FAULT INTERRUPTER.

### "BOATHOUSE" MODEL LIFT: 6,000 LB PARTS LIST ITEM DESCRIPTION NO. QTY 3/4 HP MOTOR WITH LONG CORD 15' AND BOXED SWITCH GEAR PLATE HINGED COVER OVERHEAD MOTOR ANCHOR BRACKET BEARING PIPE CARRIER BEARING PIPE CARRIER BRACKETS SPACER SLEEVE 10" PULLEY 4L360 BELT 1/2" BORE PLAIN SHEAVES 7/16" SHACKLES SNATCH BLOCKS DEAD END BRACKETS 1/4" x 40' CABLES WITH NICO AND THIMBLE 6" CRADLE BEAMS (CRADLE LIFT ONLY) ROLLS 14' CARPET (CRADLE LIFT ONLY) TIMBER RUNNER BRACKET 3/8" x 2 1/2" GALVANIZED CARRAIGE BOLTS (CRADLE LIFT ONLY) 3/8" GALVANIZED NUTS (CRADLE LIFT ONLY) 14' WEIGHTED SLINGS (SLING LIFT ONLY-NOT SHOWN) HARDWARE 1/2" x 1" GALVANIZED CARRAIGE BOLTS 1/2" x 1 1/2" GALVANIZED BOLTS 1/2" x 2" GALVANIZED BOLTS 1/2" GALVANIZED NUTS 1/2" GALVANIZED LOCK WASHERS 1/2" GALVANIZED FLAT WASHERS 3/16" WIRE CLIPS 5/8" x 3" GALVANIZED BOLTS 5/8" x 6" GALVANIZED BOLTS 5/8" GALVANIZED NUTS STAINLESS STEEL HARDWARE COVERPAK 5/8" x 3" STAINLESS STEEL BOLTS 5/8" STAINLESS STEEL LOCK NUTS 5/8" GALVANIZED WASHERS $5/8" \times 1-1/2"$ GALVANIZED HEX BOLTS 5/8" GALVANIZED LOCK WASHERS








- 1. \* CAUTION: INSTALL ONLY THE HARDENED BOLT SUPPLIED WITH THE GEAR ASSEMBLY.
- 3. FOR LIST OF MATERIALS RELATED TO PART NUMBERS, SEE PARTS LIST.




1. SEE DRAWING NO. 003 (DRUM AND MOTER MOUNT) FOR A SIDE VIEW OF MOTOR AND MOTOR HOUSING.








1. FOR LIST OF MATERIALS RELATED TO PART NUMBERS, SEE PARTS LIST.






CABLE

= BOAT LIFTS UNLIMITED, INC. =

- 1. BUNK BOARDS, IF NOT SUPPLIED, SHOULD BE  $2" \times 8"$  OR  $2" \times 10"$  DIMENSIONAL LUMBER.
- 2. FOR LIST OF MATERIALS RELATED TO PART NUMBERS, SEE PARTS LIST.



# **BOAT LIFTS UNLIMITED, INC.**

## GENERAL NOTES:

- 1. FOR OPTIMUM PERFORMANCE, EQUAL WEIGHT DISTRIBUTION IS REQUIRED OVER BOTH CRADLE ARMS.
- 2. TO OBTAIN EQUAL WEIGHT DISTRIBUTION:
- A. USE BALANCE POINT OF BOAT.
  B. DO NOT USE CENTER OF BOAT LENGTH.

